

A 400 series – Fully automatic slicer ...

A 400 (Table version)

- Stack, shingle, shave
- Programmable with up to 99 memories
- Max. stack height = 3.5"
- Shingle traditionally, transverse, multi-layer, multi-row (3)
- Adjustable distance between slices, 3 mm-50 mm
- Total shingle portion length = 10"
- Shaving with optional attachment
- Standard 13" blade
- Product size round: min. = 2", max. = 7"
- Product size rectangular: min. = 2" x 2", max. = 6.89" x 9.45"
- Product up to 15" long without re-clamping
- Multiple chubs in carriage for full production, up to 10" wide
- Slice thickness = 0.5-12 mm. Adjustable in tenths.
- Adjustable carriage speed: 30-55 strokes per minute
- Cleaning and Sharpening programs for total safety
- Two carriage lengths available, 400 mm and 600 mm
- Built in diagnostic program
- Optional mobile stand.



A 400 FB series – Fully automatic slicer ...

A 400 FB (conveyor version)

- Stack, shingle, shave
- Programmable with up to 200 memories
- Max. stack height = 2.4"
- Shingle traditionally, transverse, multi-layer, multi-row (3)
- Adjustable distance between slices, 3 mm-50 mm
- Total shingle portion length = no limits
- Shaving with optional attachment
- Standard 13" blade
- Product size round: min. = 2", max. = 7"
- Product size rectangular: min. = 2" x 2", max. = 6.89" x 9.45"
- Product up to 15" long without re-clamping
- Multiple chubs in carriage for full production, up to 10" wide
- Slice thickness = 0.5-12 mm, adjustable in tenths
- Adjustable carriage speed: 30-55 strokes per minute
- Cleaning and sharpening programs for total safety
- Two carriage lengths available: 400 mm and 600 mm
- Built in diagnostic program
- Optional mobile stand
- 4 foot long conveyor allows for maximum production
- Particularly suitable for continuous operation.

